

Machine Application Chart

Attachment	Type	Size/Model	Position	Travel		REQUIRED COMPONENTS			REFERENCE INFO.		
				STD	Req'd	Adapter & Hardware	Setting Gage	Control Valve	Mount Info.	Trip Brkt Mount Dwg	Remarks
165-OB-1											
A65X	New Britain	62	4th or 5th	2.312	2.404	165201	165079	141600	165302	160231	(1)
A65X	Wickman	2 1/4-6	4th	1.625	2.406	No Req'd	165079	141600	165300	160231	SEC 393 (2)
A65X	Wickman	2 1/4-6	5th	1.250	2.406	No Req'd	165079	141600	165300	160231	SEC 393 (2)
A65X	Wickman	7 1/4-6	4th	2.000	2.468	165201	165079	141600	165302	160231	(2)
A65X	Wickman	7 1/4-6	5th	1.750	2.468	165201	165079	141600	165302	160231	(2)
A65X	Wickman	1 3/8-6	4th	1.562	1.937	No Req'd	165079	141600	165312	160231	SEC 293 (2)
A65X	Wickman	1 3/8-6	5th	1.250	1.937	No Req'd	165079	141600	165312	160231	SEC 293 (2)
A65WM13/46	Wickman	1 3/4-6	4th	1.562	1.937	No Req'd	165079	141600	165300	160231	SEC 293 (2)
A65WM13/46	Wickman	1 3/4-6	5th	1.250	1.937	No Req'd	165079	141600	165300	160231	SEC 293 (2)
A65X	Wickman	3 1/4-6	4th	2.000	2.468	165200	165079	141600	165301	160231	SEC 593 (2)
A65X	Wickman	3 1/4-6	5th	1.750	2.468	165200	165079	141600	165301	160231	SEC 593 (2)
A65X	Wickman	3 1/2-6				160201	165079	141600	165302	160231	
A65X	Wickman	3 1/2-6				160201	165079	141600	165302	160231	
A65X	Wickman	2 5/8-6	4th	2.00	2.468	165201	165079	141600	165302	160231	SEC 593 (2)
A65X	Wickman	2 5/8-6	5th	1.750	2.468	165201	165079	141600	165302	160231	SEC 593 (2)
A65WM65/86	Wickman	6 5/8-6				165079	165079	141600	165301	160231	

- 1) Requires increased cross slide travel.
2) Requires auxiliary cross slide motion for max clearance.