

151MT Attachment Wedge Roller Combinations

Wedge	Roller	Spring	FCD Min	FDC Max	FCD Power
Narrow	0.625	Yellow/Medium	2.297	2.599	2.442
Narrow	0.688	Yellow/Medium	2.266	2.562	2.412
Narrow	0.750	Yellow/Medium	2.235	2.527	2.382
Narrow	0.813	Yellow/Medium	2.204	2.492	2.353
Narrow	0.875	Yellow/Medium	2.174	2.457	2.323
Medium	0.625	Green/Long	2.131	2.416	2.277
Medium	0.688	Green/Long	2.100	2.382	2.247
Medium	0.750	Green/Long	2.070	2.348	2.218
Medium	0.813	Green/Long	2.039	2.314	2.189
Medium	0.875	Green/Long	2.010	2.280	2.159
Large	0.625	Green/Long	1.972	2.246	2.119
Large	0.688	Green/Long	1.942	2.212	2.089
Large	0.750	Green/Long	1.912	2.180	2.060
Large	0.813	Green/Long	1.882	2.146	2.030
Large	0.875	Green/Long	1.853	2.114	2.001
X-Large	0.625	Green/Long	1.819	2.083	1.963
X-Large	0.688	Green/Long	1.789	2.051	1.934
X-Large	0.750	Green/Long	1.760	2.019	1.906
X-Large	0.813	Green/Long	1.731	1.987	1.877
X-Large	0.875	Green/Long	1.702	1.956	1.848

Application Specific Recommendations

Thread	Wedge	Roller	Spring	FCD Min	FDC Max
1/16-27	Large	0.688	Green/Long	1.985	2.059
1/8-27	Narrow	0.750	Yellow/Medium	2.270	2.344
3/8-18	Large	0.813	Green/Long	1.912	2.014
1/4-18	Narrow	0.625	Yellow/Medium	2.423	2.525
1/2-14	Narrow	0.625	Yellow/Medium	2.331	2.459