



LaserMarking Detail

REV ZONE ECN REVISION DESCRIPTION DATE ENG 3/19 PRD

120°
------

Scale	Chordal position
0.075	1.035
0.070	0.941
0.065	0.850
0.060	0.764
0.055	0.682
0.050	0.604
0.045	0.529
0.040	0.458
0.035	0.390
0.030	0.325
0.025	0.264
0.020	0.205
0.015	0.149
0.010	0.097
0.005	0.047
0.000	0.000
-0.005	-0.047
-0.010	-0.097
-0.015	-0.149
-0.020	-0.205
-0.025	-0.264
-0.030	-0.325
-0.035	-0.390
-0.040	-0.458
-0.045	-0.529
-0.050	-0.604
-0.055	-0.682
-0.060	-0.764
-0.065	-0.850
-0.070	-0.941
-0.075	-1.035

Mark Scale in 3 Places, Every 120° Visually Align -0- with roll pin within +/- 10°

PRIOR TO MARKING - SET HEAD TO CENTER OF ADJUSTMENT

- 1) Loosen 3 Hex Bolts Near Shank
- 2) Twist Head Until Fully Closed, Mark Across Both Parts w/ Sharpie
- 3) Twist Head Until Fully Open, Mark Across Both Parts w/ Sharpie
- 4) Adjust Until Mark on Head is Exactly 1/2 way Between Sharpie Marks
- 5) Tighten Hex Bolts

THIS DRAWING IS THE CONFIDENTIAL AND EXCLUSIVE PROPERTY OF C.J. WINTER MACHINE TECHNOLOGIES, DISCLOSED IN ANY WAY, WHATSOEVER TO ANYONE WITHOUT THE EXPRESS WRITTEN PERMISSION OF C.J. WINTER MACHINE TECHNOLOGIES, INC UNLAWFUL DISCLOSURE MAY RESULT IN PROSECUTION

DRAWING MUST COMPLY TO C. J. WINTER ENGINEERING STANDARD E1058 & ASME Y14.5M 1994. UNTOLERANCED DIMENSIONS ARE BASIC

.020 | A | B | C | SW | HEAT TRT: N/A

DRAWN BY: P.Diliberto DWG DATE: 03/07/2019 ENG. APPR: P.Allart APPR DATE: 03/07/2019 MATERIAL: SEE BOM

Spline Attachment (1.13 Plate Dia) DRAWING NO. (1.000 OAL Roll)